



T25 HILUX SELF-LUMINOUS ALARM CLOCK

A top quality alarm clock incorporating the very best self-luminous illumination and quartz movement technology ...

making it quick and easy to tell the time in darkness at a glance

- A more elegant alternative to the standard Firefly T25 unit
- Sixteen reliable trigelight® self-luminous light sources
- Illuminated dial, hour/minute/second/alarm hands
- Continuous illumination for 15-plus years
- Prestigious 'Rhythm' quartz movement
- Soft, step rotating movement
- Stylish, black aluminium case
- Compact and very easy to use



FIREFLY - ENHANCED SAFETY IN DARKNESS

T25 HILUX SELF-LUMINOUS ALARM CLOCK



Illumination

Each Firefly T25 HiLux Alarm Clock incorporates sixteen trigelight® Gaseous Tritium Light Sources (GTLS) which provide a reliable, safe and self-powered source of continuous radioluminescent light output. No battery power or charging by ambient light is required by the GTLS during the lifetime of the product. Each GTLS comprises a sealed borosilicate glass capsule which contains a tiny amount of gaseous tritium, the power supply for the device. Beta-particle radiation (ie. electrons released by the gaseous tritium as it decays) is harnessed to energise a phosphor coating on the inside surface of the capsule, causing it to glow. As a sealed source, they are non-emissive and of a very low energy level. Every trigelight® source light is manufactured and tested in accordance with the UK MOD Defence Standard 62/4. GTLS contain no moving parts and, because the unit is continuously energised, an off/on switch is not required. They will remain energised for more than 10 maintenance-free years, even during extended periods of complete darkness.

Specification

The T25 HiLux case is machined from a solid aluminium block, providing an attractive yet robust black enclosure.
Length: 58mm, Height: 58mm, Depth: 24mm. Weight (including battery): 120g
Battery (required for movement & alarm only): 1 Button LR44 (1.5vdc)
Battery Life: 1 year (based upon 30secs alarm per day)
Battery included, supplied isolated. The HiLux is self-starting after battery connection.
Alarm: Increasing 'beep' and auto stop (300secs) system.
Temperature Range: -10°C to +50 °C

Warranty

The clock is covered by warranty for 12 months from the date of purchase.

FIREFLY - ENHANCED SAFETY IN DARKNESS

SP2

Self Powered Safety Products
comms@sp2.uk.net
www.fireflymarkers.co.uk